



### Physical Strength

Pulling load resistance	<b>Over 19 kN</b>
ISO 17712 classification	<b>Grade H: High Security Seal</b> (suitable for C-TPAT operations) <b>Compliant with new ISO FDIS 17712</b>

### Material and Dimensions

Barrel	Core	<b>Low Carbon Steel, 18 mm diameter</b>
	Coating	<b>ABS</b>
	Overall	<b>22,5 mm long x 24 mm large x 31 mm high</b>
Pin	Core	<b>Carbon Steel, 8 mm diameter</b>
	Coating	<b>ABS</b>
	Head	<b>20 mm diameter</b>
	Sealing length	<b>45,0 mm</b>
Sealed unit total length		<b>82,0 mm</b>

### Colours and Printing

Marking zone	<b>25 mm x 18 mm</b>
Printing type	<b>Laser</b>
Printing specifications	<b>First line: Customer ID, Second line: Numbering</b>
Customer ID	<b>Alphanumeric and B&amp;W graphic logo</b>
Numbering	<b>Alphanumeric with double numbering on pin head</b>
Standard colours	<b>Light Green, Light blue, Orange, Yellow, White, Grey</b>

### Packaging

Bundle	<b>10 individual bags per band</b>
Seals per carton	<b>200 pieces in 10 bands</b>
Carton dimensions	<b>400 mm x 250 mm x 160 mm</b>
Carton weight	<b>Approx. 11 kg</b>

Universeal reserves the right to change specifications without prior notice

